

KNX OPERATING UNITS WITH TOUCH DISPLAY

							
NAME	CASA CONNECT KNX	FABRO KNX	KNX WS1000 STYLE	KNX TOUCH ONE STYLE	CORLO TOUCH KNX 5IN	CORLO TOUCH KNX	CALA TOUCH KNX (3 Models)
Item number	71200	71270	70193	70197	70481, 70475	70258-70261, 70334-70337, 70252-70255	70800, 70802, 70810, 70812, 70820, 70822
Display size	10,1" (1280 × 800 px)	7" (800 × 480 px)	8,4" (640 × 480 px)	5,7" (640 × 480 px)	5" (800 × 480 px)	3,5" (320 × 240 px)	2,3" (320 × 240 px)
Integrated sensors	–	–	–	Temperature/Humidity	–	–	T: Temperature TH: Temperature/Humidity AQS/TH: CO ₂ /Temperature/Humidity
Inputs	1x Ethernet (LAN)	–	1x Weather station P04i-GPS	4x Digital (binary data)	4x Analog/Digital (binary data or temperature sensor T-NTC)	4x Analog/Digital (binary data or temperature sensor T-NTC)	4x Analog/Digital (Binary data or temperature sensor T-NTC)
Additional communication options (additional to KNX)	LAN/WLAN for Internet (browser, remote diagnostics), WLAN for App	–	32 radio channels for Elsner RF actuators, sensors, push buttons, remote control	Radio channel for remote control Remo 8/pro	Model "WL" with WLAN interface	Model "WL" with WLAN interface	–
Manual operation on Display:				Manual operation on Display:			
Shading	✓	✓	✓	✓	✓	✓	✓
Window	✓	✓	✓	✓	✓	✓	✓
Heating/cooling	✓	✓	✓	✓	✓	✓	✓
Ventilation	✓	✓	✓	✓	✓	✓	–
Light	✓ RGB, tunable white	✓ RGB, tunable white	✓	✓	✓	✓	✓ RGB, tunable white
Scenes	✓	✓	–	–	✓	✓	✓
Operating elements & display surface individually assignable	✓	✓	–	✓	✓	✓	–
Display of operating elements selectable	–	✓	–	–	✓	✓	✓
Individual designations (names)	✓	✓	✓	✓	✓	✓	✓
Labelling with symbol	✓	✓	–	–	✓(internal library or own files)	✓(internal library or own files)	–
Screen saver	Off, Clock/Temperature, indiv. pictures, Off when room is dark	Off, Clock	Off, Off when room is dark, indiv. pictures		Off, Clock, indiv. pict., Off when room is dark	Off, Clock, indiv. pict., Off when room is dark	Off, Clock
Automatic functions:				Automatic functions:			
Shading	✓	–	✓	✓	✓	✓	–
Window	✓	–	✓	✓	✓	✓	–
Heating/Cooling	✓ (control)	–	–	✓ (control)	✓ (control)	✓ (control)	✓ (control)
Ventilation	✓	–	✓	✓	✓ (control)	✓ (control)	T: – TH, AQS/TH: ✓ (control)
Light	✓	–	✓	✓	✓	✓	–
Alarm/Security	✓	–	✓	✓	✓	✓	–
Automatic adjustable on the display	✓	–	✓	✓	✓	✓	(only room setpoint temperature, mode)
Further bus functions	–	multifunction modules (computers), AND/OR logic	–	Actuating variable comparators, multifunction modules (computers), AND/OR logic	Limit values, AND/OR logic	Limit values, AND/OR logic	Limit values, actuating variable comparators, multifunction modules (computers), AND/OR logic